Item #	

Job _____

SUPER ERECTA SHELF® MW UTILITY CARTS — TWO-SHELF MODELS

- Attractive and thoroughly practical, these carts are offered as complete units, shipped knocked down, with all components packaged in a compact carton.
- Super Erecta Shelf® Construction makes units easy to assemble with absolute rigidity, and makes relocation of shelves quick and simple.
- Choice of 15 Two-Shelf Models: Three different shelf combinations, each in five to ten different models.
 MW100 Series Two stainless steel flat shelves. Five sizes. Stainless steel handles.

MW600 Series — Two wire shelves, chrome or stainless steel. Five sizes; ten models. Handle material matches shelves.

- Wire Shelves: Bright, modern, sanitary appearance. Open construction minimizes dust accumulation, maximizes visibility and air circulation.
- **Solid Shelves:** Ideal for transporting materials that require an expanse of flat surface. Raised ship's edge permits fast clean-up in case of liquid spills. Double thickness of 18-gauge steel at edges also gives rigidity and high strength.
- Casters: Standard-duty. 4LD 4" (102mm) diameter casters on carts 15¹/₂" (393mm) and 18" (457mm) wide; 5LD 5" (127mm) diameter casters on carts 21" (533mm) and 24" (610mm) wide. See sheet #11.20 for additional information on casters.
- Donut Bumpers
- One-Piece Handle
- **Height:** 38" (965mm) floor to handle with 4" (102mm) casters; 39" (990mm) floor to handle with 5" (127mm) casters.
- Replaceable Parts: If any part of any cart is damaged by use, replacement parts are readily available and easily installed.
- Accessories: A wide variety are available to increase usefulness. See Catalog Sheets 10.04 and 10.05 for wire shelf accessories, 10.25 for solid shelf accessories.













MW Carts (Two-Shelf Models)





Dimensions

	Width Le			gth		orox. I. Wt.				Cas	sters
Cat. No.		(mm)	(in.)	(mm)	(lbs.)	(kg)	Shelves	Shelf Material	Handles	(in.)	(mm)
MW103	18	457	24	610	40	18.1	2-Solid	Stainless Steel	Stainless Steel	4	102
MW104	18	457	30	760	45	20.4	2-Solid	Stainless Steel	Stainless Steel	4	102
MW105	18	457	36	914	48	21.8	2-Solid	Stainless Steel	Stainless Steel	4	102
MW106	21	533	36	914	54	24.5	2-Solid	Stainless Steel	Stainless Steel	5	127
MW108	24	610	36	914	60	27.2	2-Solid	Stainless Steel	Stainless Steel	5	127
MW601	18	457	24	610	34	15.4	2-Wire	Chrome	Chrome	4	102
MW602	18	457	24	610	34	15.4	2-Wire	Stainless Steel	Stainless Steel	4	102
MW603	18	457	30	760	37	16.8	2-Wire	Chrome	Chrome	4	102
MW604	18	457	30	760	37	16.8	2-Wire	Stainless Steel	Stainless Steel	4	102
MW605	18	457	36	914	40	18.1	2-Wire	Chrome	Chrome	4	102
MW606	18	457	36	914	39	17.7	2-Wire	Stainless Steel	Stainless Steel	4	102
MW607	21	533	36	914	44	20.0	2-Wire	Chrome	Chrome	5	127
MW608	21	533	36	914	44	20.0	2-Wire	Stainless Steel	Stainless Steel	5	127
MW611	24	610	36	914	47	21.3	2-Wire	Chrome	Chrome	5	127
MW612	24	610	36	914	46	20.9	2-Wire	Stainless Steel	Stainless Steel	5	127

Load Rating: 375 lbs. (170kg) on units with 4LD and 5LD casters.

All Metro Catalog Sheets are available on our Web Site: www.metro.com



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705 Phone: 570-825-2741 Fax: 570-825-2852

Asia/Pacific: +65.6567.8003 For Product Information: Latin America: 1.561.333.3824 U.S. and Canada: 1.800.433.2232 Europe: +31.76.587.7550 Middle East/Africa: +971.4.811.8286

Copyright © 2009 InterMetro Industries Corp.

Printed in U.S.A. Rev. 11/09 Information and specifications are subject to change without notice. Please confirm at time of order.