Item #



Job ___

Starsys[®] Mobile Products Polymer Casters

The Starsys standard, polymer, plate casters offer customer maintenance free, medical grade casters that are easy smooth rolling, quiet, and robust. All Starsys mobile products have these standard 5-inch plate casters and come with two (2) total locking casters in the front of the unit and two (2) directional (0 deg / 90 deg locking) in the rear of a unit. These casters greatly assist in controlled mobility and positioning of carts (short or tall) and mobile work centers.

Features

- B-Plate caster standard on all Starsys mobile products.
- Maintenance free, with sealed wheel bearings, polymer construction.
- Corrosion resistant with non-marking wheel.
- · Resistant to water.
- Medical Grade caster specifically designed for all environments where silence is essential.
- Color coded caster for locking type (total lock is red, directional is green).
- Thread guard prevents caster failure from strings and other debris.
- Ball bearing swivel head.









All Metro Catalog Sheets are available on our website: www.metro.com



InterMetro Industries Corporation North Washington Street, Wilkes-Barre, PA 18705 Product Information. U.S. and Canada: 1.800.992.1776 Outside U.S. and Canada: www.metro.com/contactus

LO2-257 Printed in U.S.A. Rev. 4/22

Information and specifications are subject to change without notice. Please confirm at time of order. Job

Starsys[®] Mobile Products **Polymer Casters**

(NSF.)

Front Caster - Total Locking 5" B-plate with green brake lever, caster material nylon 6, color-matched.

Wheel Style	Wheel Diameter	Wheel Hub	Tread	Load Capacity	Temperature Rating	Bearing Type	Top Plate	Plate Style	Replacement Part Numbers
Swivel, total locking	5" (127mm)	Polyolefin	Thermoplastic Rubber TPR tread	300 lbs. (136 kg) per caster	-14°F - 104°F (-26°C - 40°C)	Precision Ball Bearing	Zinc Plated	B-Plate	RPC02-397

NOTE: Maximum load for 4 casters is 900 lbs.

Rear Caster - Directional Locking (NSF)

5" B-plate with green brake lever, caster material nylon 6, color-matched.

Wheel Style	Wheel Diameter	Wheel Hub	Tread	Load Capacity	Temperature Rating	Bearing Type	Top Plate	Plate Style	Replacement Part Numbers
Swivel, directional locking	5" (127mm)	Polyolefin	Thermoplastic Rubber TPR tread	300 lbs. (136 kg) per caster	-14°F - 104°F (-26°C - 40°C)	Precision Ball Bearing	Zinc Plated	B-Plate	RPC02-398

NOTE: Maximum load for 4 casters is 900 lbs.





an Ali Group Company





